



CR 10E

125KHz Proximity Card Reader



USB Interface


Proximity Card Enrollment Reader

- 125KHz Proximity Card Reader
- Read Range: Up to 2cm (125 KHz)
- Reads card number only
- USB interface
- Powered by USB
- LED indicator and buzzer feedback
- Avoid manual input mistake
- Compatible with Microsoft Windows® 98 or Newer


Part Numbers

CR 10E 125KHz Prox Card Reader

What's in the Box



CR10E



USB Cable

Specifications

Read Range: Up to 2cm

Power / Current: USB 5V DC / Max.100mA

LED Indicator: 2 Color LED Indicators (Red & Green)

Beeper: Yes

Color: Black

Interface

USB

Supported OS

Microsoft Windows® 98 or Newer

Environment

Operating Temperature:

14° F to 158° F (-10° C to 70° C)

Operating Humidity:

10% to 90% relative humidity non-condensing

Dimensions

Width: 5.5 in. (14 cm)

Height: 3.9 in. (10 cm)

Depth: 1.18 in. (3 cm)

Weight: 0.264 lbs. (120 g)



Design and Specifications subject to change without notice

© Copyright 2019. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

ZKTeco

200 Centennial Avenue, Suite 211, Piscataway, NJ 08854, USA

+1 732-412-6007 ext: 215 +1 732-412-6008

workday@zktechnology.com | workdayclocks.com