

RFID/ Prox Credentials


RFID/prox credentials can be used with any ZK readers which has a 125 KHz prox card reader.




Key Fob



Disc



Thick / Clamshell Card



Thin / ISO Card

Customers sometimes are already using existing non-ZK card readers and cards, ZK also provides 125 KHz key fobs which can be clipped on to cards having a badge clip slot; And for customers having non-ZK cards with no badge clip slot, we also offer 125 KHz self-adhesive RFID discs

Notes

When ordering ZK readers, be sure to specify which card reader technology and cards you need PRIOR to placing your order.

Specifications

Interface

EM-4100 series prox cards with a EM / Marin S.A. memory chip.
125 KHz (generic prox 26 bit, Read-only)
Passive prox/RFID responder

Dimensions

Thick clamshell card

Length: 3.36 in. (85.47 mm)
Width: 2.12 in. (53.85 mm)
Thickness: 0.77 in.(1.97 mm)
Badge clip slot: 0.63 in. x 0.13 in. (16 mm x 3.3 mm)

Key Fob:

1.37 in. x 0.91 in. x 0.15 in. (34.8 mm x 23 mm x 3.9 mm)

RFID disk:

Diameter: 7/8 in. (22.22 mm)
Thickness: 1/16 in. (1.59 mm)

Thin ISO card

Length: 3.36 in. (85.47 mm)
Width: 2.12 in. (53.85 mm)
Thickness: 0.03 in. (0.8 mm)
Badge clip slot: 0.63 in. x 0.13 in. (16 mm x 3.30 mm)

© Copyright 2018. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

Design and Specifications subject to change without notice

ZKTeco

201 Circle Drive North, Suite 116, Piscataway, NJ 08854, USA

+1 732-412-6007 +1 732-412-6008

sales@zktechnology.com | zktechnology.com

