



# US760

## Time & Attendance Terminal

### Fingerprint & Proximity Card Reader



Fingerprint



PIN



RFID

## Specifications

### Capacity

Users: 3,000  
ID Cards: 3,000  
Fingerprint: 3,000  
Records: 50,000

### Display

2.8 in. TFT Color Screen

### Communications

TCP/IP, WiFi, USB-host

### Standard Functions

9 Digit User ID, T9 Input, SMS, DST, Self-Service Query, Automatic Status Switch, Ring bell

### Optional Functions

ID/Mifare, WDMS, RS232 External Printer

### Access Control Interface

3rd Party Electric Lock, Exit Button

### Power

12 V DC, 1.5 A


### Environment

Operating Temperature: 32° F to 113° F (0° C to 45° C)  
Operating Humidity: 20% to 80%


### Dimensions

Width : 7.32 in. (18.6 cm)  
Height: 5.43 in. (13.8 cm)  
Depth: 1.7 in. (4.3 cm)


## What's in the Box




US760



Back Plate



AC Power Adapter



Screws & Anchors



Design and Specifications subject to change without notice

ZKTeco

200 Centennial Avenue, Suite 211, Piscataway, NJ 08854, USA

+1 732-412-6007 +1 732-412-6008

sales@zktechnology.com | zktechnology.com

© Copyright 2022. ZK Technology LLC. Dba. ZKTeco. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.